

Mobile Field Shelter - Hunter

Timber sizes nominal before planning and processing, other dimensions may vary dependant on individual building.

Ridge Height:	3.01m excluding Onduline
Eaves Height:	2.46m excluding Onduline
Threshold Height:	138mm
Opening Size:	1.88m (w) x 2.09m (h) – from ground to top of opening is 2.228m
Overhang:	With 1.2m overhang lined with plywood (1.35 with Gutter)
Skid:	100 x 100mm galvanised skid with towing points at either end
Framework:	Constructed from 100x50mm cls Tanalith E treated timber at 600mm centres. Studwork doubles at door apertures. Additional 100x50mm cls cross members at 1.22m height.
Cladding:	Premium ex19x125mm tanalith E treated overlap shiplap, fixed with 45mm sheradized ring shanked nails
Kick-boarding:	Lined to 1.22m with 12mm plywood
Roof trusses:	All trusses fixed to sections with 100mm or 150mm timberlock screws
Purlins:	100x50mm or 125x50mm positioned at a maximum of 600mm centres dependant on roof span
Roofing:	Black Onduline with Onduline ridge capping lined with 11mm OSB
Guttering:	112mm black upvc guttering fitted with one 68mm downpipe to either end of front elevation
Partition:	Not included

Mobile Combination units

(as field shelter with the following differences for the tack room section)

Opening:	Tack room door width 0.90m wide x 2.1m high
Interior Lining:	All walls are fully lined to eaves with 9mm hardwood faced ply
Door:	Supplied and fitted with three 600mm T hinges, 150mm Brenton bolt and cabin hook to secure door when open.
Floor:	100x50mm tanalith E treated joists covered with 125x22mm sawn Tanalith E treated floorboards or 18mm OSB
Roof lining:	Face of truss between stable and tack room also boarded with hardwood faced ply.

Mobile Tack room

(as mobile field shelter with the following differences)

Interior Lining:	All walls are fully lined to eaves height with 9mm hardwood faced ply
Door:	Supplied and fitted with three 24" T hinges, 6" Brenton bolt and cabin hook to secure door when open.
Floor:	100x50mm Tanalith E treated joists covered with 125 x 22mm sawn Tanalith E treated floorboards or 18mm OSB
Roof lining:	11mm OSB