

Tel: 01789 400988

Email: enquiries@redmire.co.uk

Mobile Field Shelter - Harrier

Timber sizes nominal before planning and processing, other dimensions may vary dependant on individual building.

Ridge Height: 3.0m Eaves Height: 2.4m Threshold Height: 80mm

Opening Size: 1.880mm (w) x 2.090m (h) – from ground to top of opening is

2.170m

Overhang: 1050mm overhang lined with plywood (1200 mm inc gutter)
Skid: 80 x 40mm galvanised skid with towing points at either end

Framework: Constructed from 75x50mm cls tanalith E treated timber at 600mm

centres. Studwork doubles at door apertures, additional cross

members at 1.22m height.

Cladding: Premium ex19x125mm tanalith E treated overlap shiplap, fixed with

45mm sheradized ring shanked nails

Kick-boarding: Lined to 1.22m with 18mm OSB

Roof trusses: All trusses fixed to sections with 100mm or 150mm timber lock

screws

Purlins: 100x50mm or 125x50mm positioned at a maximum of 600mm

centres dependant on roof span

Roofing: Black Onduline with Onduline ridge capping lined with 11mm OSB Guttering: 112mm black uPVC guttering fitted with 68mm downpipes to both

ends of front elevation

Partition: Not included

Mobile Combination units

(As field shelter with the following differences for the Tack room section)

Opening: Tackroom door width 0.90m wide x 2.1m high

Interior Lining: Unlined

Door: Supplied and fitted with three 16" T hinges, 6" Brenton bolt and

cabin hook to secure door when open.

Floor: 100 x 50mm tanalith E treated joists at a maximum 600mm

centres. Covered with 125x22mm sawn tanalith E treated

floorboards or 18mm OSB

Roof lining: Face of truss between stable and tack room also boarded with

11mm OSB

Mobile Tack room

(As mobile field shelter with the following differences)

Interior Lining: All walls are fully lined to eaves height with 11mm OSB

Door: Supplied and fitted with three 16" T hinges, 6" Brenton bolt and

cabin hook to secure door when open.

Floor: 100x50mm tanalith E treated joists at a maximum 600mm centres.

Covered with 150 x 28mm sawn Tanalith E treated floorboards

Roof lining: 11mm OSB.